



# KEGEL LANDMARK PATTERNS

## SPORT SERIES




### S - Alcatraz



Oil Pattern Distance	<b>38</b>	Reverse Brush Drop	<b>38</b>	Oil Per Board	<b>Multi ul</b>
Forward Oil Total	<b>13.695 mL</b>	Reverse Oil Total	<b>11.15 mL</b>	Volume Oil Total	<b>24.845 mL</b>
Tank Configuration	<b>N/A</b>	Tank A Conditioner	<b>FIRE</b>	Tank B Conditioner	<b>ICE</b>


	START	STOP	LOADS	MICS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	5	45	14	3	B	185	0.0	7.9	7.9	8325
2	6L	6R	2	45	14	3	B	58	7.9	11.8	3.9	2610
3	8L	8R	1	40	18	3	B	25	11.8	14.3	2.5	1000
4	9L	9R	1	40	18	3	B	23	14.3	16.8	2.5	920
5	10L	10R	1	40	18	3	B	21	16.8	19.3	2.5	840
6	2L	2R	0	40	18	3	B	0	19.3	32.0	12.7	0
7	2L	2R	0	40	30	2	B	0	32.0	38.0	6.0	0

	START	STOP	LOADS	MICS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	40	30	1	B	0	38.0	34.0	-4.0	0
2	17L	17R	3	40	18	3	B	21	34.0	26.4	-7.6	840
3	10L	10R	1	40	18	3	B	21	26.4	23.9	-2.5	840
4	9L	9R	1	40	18	3	B	23	23.9	21.4	-2.5	920
5	8L	8R	2	45	18	4	B	50	21.4	16.3	-5.1	2250
6	6L	6R	1	45	18	4	B	29	16.3	13.8	-2.5	1305
7	2L	2R	3	45	14	4	B	111	13.8	7.9	-5.9	4995
8	2L	2R	0	45	14	4	B	0	7.9	0.0	-7.9	0



Cleaner Ratio Main Mix 4:1  
 Cleaner Ratio Back End Mix 4:1  
 Cleaner Ratio Back End Distance 59  
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 60

Item	3L-7L-18L-18R	8L-12L-18L-18R	13L-17L-18L-18R	18L-18R-17R-13R	18L-18R-12R-8R	18L-18R-7R-3R
Description	Outside Track/Middle	Middle Track/Middle	Inside Track/Middle	Middle/Inside Track	Middle/Middle Track	Middle/Outside Track
Track Zone Ratio	2.19	1.23	1.12	1.12	1.23	2.19



This page shows the **KOSI FLEX LANE MACHINE** program sheet.

The **HEADER** shows the oil pattern distance, the reverse brush drop distance, the amount of lane conditioner applied to the lane, the oil per board setting, and the conditioner type in each tank.

Below that is the **FLEX LANE MACHINE PROGRAM** settings which shows the load structure and number of loads, the oil pump setting if using the multi mic stream feature, the speed of the lane machine, the buffer speed, and the tank choice per load screen.

The **OVERHEAD CHART** on the far right shows where the conditioner is applied on both the forward and reverse pass. The gradient area is a calculation of how the conditioner might bleed off the buffer brush.

The **COMPOSITE GRAPH** at the bottom shows the total amount of conditioner applied to every board along with that volume ratio in different zones.

A good way to think about the composite graph is to envision all the conditioner on the lane being pushed back to the foul line. Once all the conditioner is stacked up, this is what it would look like.

**KEGEL TIP** - Once the amount of conditioner on the corners (outsides) reaches 300 microliters, an oil pattern begins to become "competitive". Less than that amount the ball might see friction and it could play on the easy side.